


ENS-HDMICB3M



ELECTRICAL TEST:

- 1) 100%, OPEN&SHORT WITH MISS WIRE TEST
- 2). TEST CONDITION:
 - a). CONDUCTION RESISTANCE:5 Ω Max:
 - b). INSULATION RESISTANCE: 10M Ω (Min)
 - c). TEST_VOLTAGE:DC_300V/0.01SEC
 - d).3840*2160 30HZ

Material Mumber	Length
ENS-HDMICB1M	1000 ± 30
ENS-HDMICB3M	3000 ± 30

Pin Assignment					
P1		P2	P1	P2	
1-0-	Green	0 1	19 6 Gre	een 19	
3 <u> </u>	White	8_3	14 (8) Whi	ite (8) ₁₄	
4-0-	Green	0-4	17 Dra	nin 🗾 17	
6 <u> </u>	White	<u>8</u> 6	13	<u>te</u> _13	
7-0-	Green	0-7	15 Bl	<u>ue</u> 15	
9 <u> </u>	White	X -9	16-Yel	low16	
10-0-	Green	0-10	18	ed18	
12-8-	White	8 12	Shell Drain	Wire Shell	

Conector: HDMI A Type Plug, insulator black gold plated contact gold plated

CABLE:

30AWG[(1/0.254CCS+FPE)*1P+D(1/0.254CCS+HDPE)+AL]*1P+ (1/0.254CCS+FPE)*4P1/0.254CCS*4C+AL+D(1/0.254CCS)+B(80*0.12ALM) BLACK OD:6. Omm Printing White:High Speed HDMI Cable With Ethernet